



Profile-Z

Grodzice

ArcelorMittal

	Szerokość		Wysokość		Grubości ścianek		Ciężar		Moment bezwładności	Sprężysty wskaźnik wytrzymałości
	b	h	t _r	t _w	poj. grodzicy	ściany	cm ⁴ /m	cm ³ /m		
	mm	mm	mm	mm	kg/m	kg/m ²	cm ⁴ /m	cm ³ /m		
AZ[®]-800										
AZ 18-800	800	449	8.5	8.5	80.7	100.9	41 320	1 840		
AZ 20-800	800	450	9.5	9.5	88.6	110.7	45 050	2 000		
AZ 22-800	800	451	10.5	10.5	96.4	120.5	48 790	2 165		
AZ 23-800	800	474	11.5	9.0	94.6	118.2	55 260	2 330		
AZ 25-800	800	475	12.5	10.0	102.6	128.2	59 410	2 500		
AZ 27-800	800	476	13.5	11.0	110.5	138.1	63 570	2 670		
AZ[®]-750										
AZ 28-750	750	509	12.0	10.0	100.8	134.4	71 540	2 810		
AZ 30-750	750	510	13.0	11.0	108.8	145.0	76 670	3 005		
AZ 32-750	750	511	14.0	12.0	116.7	155.6	81 800	3 200		
AZ[®]-700 & AZ[®]-770										
AZ 12-770	770	344	8.5	8.5	72.6	94.3	21 430	1 245		
AZ 13-770	770	344	9.0	9.0	76.1	98.8	22 360	1 300		
AZ 14-770	770	345	9.5	9.5	79.5	103.2	23 300	1 355		
AZ 14-770-10/10	770	345	10.0	10.0	82.9	107.7	24 240	1 405		
AZ 12-700	700	314	8.5	8.5	67.7	96.7	18 880	1 205		
AZ 13-700	700	315	9.5	9.5	74.0	105.7	20 540	1 305		
AZ 13-700-10/10	700	316	10.0	10.0	77.2	110.2	21 370	1 355		
AZ 14-700	700	316	10.5	10.5	80.3	114.7	22 190	1 405		
AZ 17-700	700	420	8.5	8.5	73.1	104.4	36 230	1 730		
AZ 18-700	700	420	9.0	9.0	76.5	109.3	37 800	1 800		
AZ 19-700	700	421	9.5	9.5	80.0	114.3	39 380	1 870		
AZ 20-700	700	421	10.0	10.0	83.5	119.3	40 960	1 945		
AZ 24-700	700	459	11.2	11.2	95.7	136.7	55 820	2 430		
AZ 26-700	700	460	12.2	12.2	102.9	146.9	59 720	2 600		
AZ 28-700	700	461	13.2	13.2	110.0	157.2	63 620	2 760		
AZ 26-700N	700	460	13.5	10.0	96.9	138.5	59 790	2 600		
AZ 36-700N	700	499	15.0	11.2	118.6	169.5	89 610	3 590		
AZ 38-700N	700	500	16.0	12.2	126.4	180.6	94 840	3 795		
AZ 40-700N	700	501	17.0	13.2	134.2	191.7	100 080	3 995		
AZ 42-700N	700	499	18.0	14.0	142.1	203.1	104 930	4 205		
AZ 44-700N	700	500	19.0	15.0	149.9	214.2	110 150	4 405		
AZ 46-700N	700	501	20.0	16.0	157.7	225.3	115 370	4 605		
AZ 48-700	700	503	22.0	15.0	158.5	226.4	119 650	4 755		
AZ 50-700	700	504	23.0	16.0	166.3	237.5	124 890	4 955		
AZ 52-700	700	505	24.0	17.0	174.1	248.7	130 140	5 155		
AZ[®]										
AZ 18	630	380	9.5	9.5	74.4	118.1	34 200	1 800		
AZ 18-10/10	630	381	10.0	10.0	77.8	123.4	35 540	1 870		
AZ 26	630	427	13.0	12.2	97.8	155.2	55 510	2 600		

Zmniejsz negatywny wpływ inwestycji na środowisko dzięki **EcoSheetPile™ Plus**.



Profile-U

Grodzice

ArcelorMittal

	Szerokość		Wysokość		Grubości ścianek		Ciężar		Moment bezwładności	Sprężystość wskaźnik wytrzymałości
	b	h	t _r	t _w	poj. grodzicy					
					ściany	kg/m ²				
mm	mm	mm	mm	kg/m	kg/m ²	cm ⁴ /m	cm ³ /m			
AU™										
AU 14	750	408	10.0	8.3	779	103.8	28 680	1 405		
AU 16	750	411	11.5	9.3	86.3	115.0	32 850	1 600		
AU 18	750	441	10.5	9.1	88.5	118.0	39 300	1 780		
AU 20	750	444	12.0	10.0	96.9	129.2	44 440	2 000		
AU 23	750	447	13.0	9.5	102.1	136.1	50 700	2 270		
AU 25	750	450	14.5	10.2	110.4	147.2	56 240	2 500		
PU®										
PU 12	600	360	9.8	9.0	66.1	110.1	21 600	1 200		
PU 12S	600	360	10.0	10.0	71.0	118.4	22 660	1 260		
PU 18 ⁻¹	600	430	10.2	8.4	72.6	121.0	35 950	1 670		
PU 18	600	430	11.2	9.0	76.9	128.2	38 650	1 800		
PU 18 ⁺¹	600	430	12.2	9.5	81.1	135.2	41 320	1 920		
PU 22 ⁻¹	600	450	11.1	9.0	81.9	136.5	46 380	2 060		
PU 22	600	450	12.1	9.5	86.1	143.6	49 460	2 200		
PU 22 ⁺¹	600	450	13.1	10.0	90.4	150.7	52 510	2 335		
PU 28 ⁻¹	600	452	14.2	9.7	97.4	162.3	60 580	2 680		
PU 28	600	454	15.2	10.1	101.8	169.6	64 460	2 840		
PU 28 ⁺¹	600	456	16.2	10.5	106.2	177.1	68 380	3 000		
PU 32 ⁻¹	600	452	18.5	10.6	109.9	183.2	69 210	3 065		
PU 32	600	452	19.5	11.0	114.1	190.2	72 320	3 200		
PU 32 ⁺¹	600	452	20.5	11.4	118.4	197.3	75 410	3 340		
GU®										
GU 6N	600	309	6.0	6.0	41.9	69.9	9 670	625		
GU 7N	600	310	6.5	6.4	44.1	73.5	10 450	675		
GU 7S	600	311	7.2	6.9	46.3	77.1	11 540	740		
GU 7HWS	600	312	7.3	6.9	47.4	79.1	11 620	745		
GU 8N	600	312	7.5	7.1	48.5	80.9	12 010	770		
GU 8S	600	313	8.0	7.5	50.8	84.6	12 800	820		
GU 10N	600	316	9.0	6.8	55.8	93.0	15 700	995		
GU 11N	600	318	10.0	7.4	60.2	100.4	17 450	1 095		
GU 12N	600	320	11.0	8.0	64.6	107.7	19 220	1 200		
GU 13N	600	418	9.0	7.4	59.9	99.8	26 590	1 270		
GU 14N	600	420	10.0	8.0	64.3	107.1	29 410	1 400		
GU 15N	600	422	11.0	8.6	68.7	114.5	32 260	1 530		
GU 16N	600	430	10.2	8.4	72.6	121.0	35 950	1 670		
GU 18N	600	430	11.2	9.0	76.9	128.2	38 650	1 800		
GU 20N	600	430	12.2	9.5	81.1	135.2	41 320	1 920		
GU 21N	600	450	11.1	9.0	81.9	136.5	46 380	2 060		
GU 22N	600	450	12.1	9.5	86.1	143.6	49 460	2 200		
GU 23N	600	450	13.1	10.0	90.4	150.7	52 510	2 335		
GU 27N	600	452	14.2	9.7	97.4	162.3	60 580	2 680		
GU 28N	600	454	15.2	10.1	101.8	169.6	64 460	2 840		
GU 30N	600	456	16.2	10.5	106.2	177.1	68 380	3 000		
GU 31N	600	452	18.5	10.6	109.9	183.2	69 210	3 065		
GU 32N	600	452	19.5	11.0	114.1	190.2	72 320	3 200		
GU 33N	600	452	20.5	11.4	118.4	197.3	75 410	3 340		
GU 16-400	400	290	12.7	9.4	62.0	154.9	22 580	1 560		
GU 18-400	400	292	15.0	9.7	69.3	173.3	26 090	1 785		